

K1050i FT

FIELD TARGET FOR PERFECTIONISTS



PRODUCT HIGHLIGHTS



- Developed together with professionals for highest precision in Field Target competitions
- Perfect image quality, even at 50 x magnification
- Parallax wheel integrated into the elevation turret (patented) 8 - 60 m
- Illuminated reticle with fine structure for maximum precision
- Also available with silver coating

The K1050i FT offers a uniquely precise experience. With the special parallax focus ranging from 9 to 66 yards (8 to 60 metres) and an illuminated reticle in the 2nd focal plane, it has been optimally designed for Field Target competitions.

TECHNICAL DATA

Magnification:	10 - 50
Objective lens diameter:	56 mm
Eye relief:	95 mm
Field of view:	2.9 - 0.6 m/100 m
Diopter compensation:	+2 / -3.5 dpt
Twilight factor (DIN 58388):	23.6 - 52.9
Impact correction per click:	1/8 MOA
Adjustment range (E/W):	1.6 / 1.2 m
Parallax adjustment:	8 - 60 m
Tube diameter:	30 mm
Length:	429 mm
Weight:	1040 g
Focal plane:	2
Illuminated:	Ja
Warranty:	10 years

FEATURES



2nd focal plane




Main tube 30 mm



Adjustment direction
CCW




MOA



Windage right

RETICLES / SUBTENSIONS



MHR