

# K624i



PROFESSIONAL CHOICE FOR LONG DISTANCES

## PRODUCT HIGHLIGHTS



- Wide field of view, exceptionally comfortable eyepiece and high contrast image
- Precise, clearly defined click mechanism and reliable repeat accuracy
- Optional left or right side windage
- Parallax wheel integrated into the elevation turret (patented) (50 m to  $\infty$ )
- Precise illuminated reticles in 1st focal plane

The K624i sets standards in handling and ergonomics thanks to the unique arrangement of its operating elements. It offers outstanding optical performance, mechanical perfection and a unique range of well proven reticles for professionals and competition shooters.

## TECHNICAL DATA

<b>Magnification:</b>	6 - 24
<b>Objective lens diameter:</b>	56 mm
<b>Exit pupil:</b>	9.4-2.3 mm
<b>Eye relief:</b>	90 mm
<b>Field of view:</b>	6.8 - 1.7 m/100 m
<b>Diopter compensation:</b>	+2 / -3.5 dpt
<b>Twilight factor (DIN 58388):</b>	18.3 - 36.7
<b>Adjustment range (E/W):</b>	2.5/1.1 m/100 m
<b>Parallax adjustment:</b>	50 m till $\infty$
<b>Tube diameter:</b>	34 mm
<b>Length:</b>	405 mm
<b>Weight:</b>	950 g
<b>Focal plane:</b>	1
<b>Illuminated:</b>	Ja
<b>Warranty:</b>	10 years

## FEATURES



1st focal plane



Main tube 34 mm



Adjustment direction  
CW or CCW



Windage left or right




Zero Stop




MIL


## RETICLES / SUBTENSIONS




MSR/Ki



Mil3




Mil4




SKMR



SKMR3



AMR



MOAK